

Chapter 4

Solved Problems

Problem 1

Script file:

```
clear, clc
T=input('Please enter the temperature in deg F: ');
R=input('Please enter the relative humidity in percent: ');
HI=-42.379+2.04901523*T+10.14333127*R-0.22475541*T*R-6.83783e-3*T^2 ...
    - 5.481717e-2*R^2+1.22874e-3*T^2*R + 8.5282e-4*T*R^2-1.99e-6*T^2*R^2;
fprintf('\nThe Heat Index Temperature is: %.0f\n',HI)
```

Command Window:

```
Please enter the temperature in deg F: 90
Please enter the relative humidity in percent: 90
```

```
The Heat Index Temperature is: 122
```

Problem 2

Script file:

```
clear, clc
format bank
F=100000; r=4.35; years=5:10;
%convert percent to decimal
r=r/100;
monthly_deposit=F*(r/12)./((1+r/12).^(12*years)-1);
tbl=[years' monthly_deposit'];
disp('           Monthly')
disp('           Years      Deposit')
disp(tbl)
```

Command Window:

Years	Monthly Deposit
5.00	1494.99
6.00	1218.02
7.00	1020.55
8.00	872.78
9.00	758.13
10.00	666.67

Problem 3

Script file:

```
clear, clc
%40 minutes is 2/3 hour
format short g
k=1.5*log(2);
t=2:2:24;
Number_of_bacteria=exp(k*t)
```

Command Window:

```
Number_of_bacteria =
  Columns 1 through 5
           8           64           512           4096           32768
  Columns 6 through 10
 2.6214e+05  2.0972e+06  1.6777e+07  1.3422e+08  1.0737e+09
  Columns 11 through 12
 8.5899e+09  6.8719e+10
```

Problem 4

Script file:

```
clear, clc
format short g
r2=12:4:28;
r1=0.7*r2;
S=pi^2*(r2.^2-r1.^2);
V=1/4*pi^2*(r1+r2).*(r2-r1).^2;
tbl=[r2' r1' V' S'];
disp('          Outer          Inner          Surface')
disp('          Radius          Radius          Volume          Area')
disp('          (in)          (in)          (in^3)          (in^2)')
disp(tbl)
```

Command Window:

Outer Radius (in)	Inner Radius (in)	Volume (in ³)	Surface Area (in ²)
12	8.4	652.34	724.82
16	11.2	1546.3	1288.6
20	14	3020.1	2013.4
24	16.8	5218.7	2899.3
28	19.6	8287.2	3946.3

Problem 5

Script file:

```
clear, clc
format short g
W=500; L=120; h=50;
x=10:20:110;
Tension=W*L*sqrt(h^2+x.^2)./(h*x)
```

Command Window:

```
Tension =
  Columns 1 through 5
    6118.8    2332.4    1697.1    1474.7    1372.8
  Column 6
    1318.2
```

Problem 6

Script file:

```
clear, clc
grades=input('Please enter the grades as a vector [x x x]: ');
number=length(grades);
aver=mean(grades);
standard_dev=std(grades);
middle=median(grades);
fprintf('\nThere are %i grades.\n',number)
fprintf('The average grade is %.1f.\n',aver)
fprintf('The standard deviation is %.1f.\n',standard_dev)
fprintf('The median grade is %.1f.\n',middle)
```

Command Window:

```
Please enter the grades as a vector [x x x]: [92 74 53 61 100 42 80 66 71 78
91 85 79 68]
```

```
There are 14 grades.
The average grade is 74.3.
The standard deviation is 15.8.
The median grade is 76.0.
```

Problem 7

Script file:

```
clear, clc
format short g
h=4:4:40; theta=[2 2.9 3.5 4.1 4.5 5 5.4 5.7 6.1 6.4];
R=h.*cosd(theta)./(1-cosd(theta));
average=mean(R);
disp('The average estimated radius of the earth in km is:')
disp(average)
```

Command Window:

```
The average estimated radius of the earth in km is:
    6363.1
```

Problem 8

Script file:

```
clear, clc
k=log(0.5)/13.3;
t=0:4:48;
ratio=exp(k*t)
```

Command Window:

```
ratio =
Columns 1 through 7
    1.0000    0.8118    0.6591    0.5350    0.4344    0.3526    0.2863
Columns 8 through 13
    0.2324    0.1887    0.1532    0.1244    0.1010    0.0820
```

Problem 9

Script file:

```
clear, clc
L=input('Please enter the mortgage amount: ');
N=input('Please enter the number of years: ');
r=input('Please enter the interest rate in percent: ');
P=L*(r/1200)*(1+r/1200)^(12*N)/((1+r/1200)^(12*N)-1);
fprintf('\nThe monthly payment of a %i years %.2f mortgage\n',N,L)
fprintf('with interest rate of %.2f percent is $%.2f\n',r,P)
```

Command Window:

```
Please enter the mortgage amount: 250000
Please enter the number of years: 30
Please enter the interest rate in percent: 4.5
```

```
The monthly payment of a 30 years 250000.00 mortgage
with interest rate of 4.50 percent is $1266.71
```

Problem 10

Script file:

```
clear, clc
format bank
A=20000; r=6.5; P=391.32; month=6:6:60;
B=A*(1+r/1200).^month-P*1200/r*((1+r/1200).^month-1);
perc=100*B/A;
tbl=[month' B' perc'];
disp('
      Balance      Remaining')
disp('      Month      $      %')
disp(tbl)
```

Command Window:

	Balance	Remaining
Month	\$	%
6.00	18278.92	91.39
12.00	16501.14	82.51
18.00	14664.80	73.32
24.00	12767.96	63.84
30.00	10808.63	54.04
36.00	8784.76	43.92
42.00	6694.22	33.47
48.00	4534.80	22.67
54.00	2304.25	11.52
60.00	0.21	0.00

Problem 11

Script file:

```
clear, clc
format short g
alt=-500:500:10000;
p=29.921*(1-6.8753e-6*alt);
Tb=49.16*log(p)+44.932;
tbl=[alt' Tb'];
disp('                Boiling')
disp('      Altitude  Temperature')
disp('      (ft)        (degF)')
disp(tbl)
```

Command Window:

Altitude	Boiling Temperature
(ft)	(degF)
-500	212.17
0	212.01
500	211.84
1000	211.67
1500	211.5
2000	211.32
2500	211.15
3000	210.98
3500	210.81
4000	210.63
4500	210.46
5000	210.29
5500	210.11
6000	209.93
6500	209.76
7000	209.58
7500	209.4
8000	209.22
8500	209.04
9000	208.87
9500	208.68
10000	208.5

Problem 12

Script file:

```
clear, clc
a=10:.1:120;
h=2*600./a;
theta=atan(a./(2*h));
height=h+2+2./sin(theta);
base=2*height.*tan(theta);
[min_area indx] = min(0.5*base.*height);
inner_base=a(indx)
inner_height=h(indx)
outer_base=base(indx)
outer_height=height(indx)
```

Command Window:

```
inner_base =
    37.2000
inner_height =
    32.2581
outer_base =
    44.1237
outer_height =
    38.2620
```

Problem 13

Script file:

```
clear, clc
a=5:.25:100; R=55;
b=sqrt((2*R)^2-a.^2);
h=b-20; w=a-8;
[max_area indx] = max(h.*w);
width_a=a(indx)
height_b=b(indx)
```

Command Window:

```
width_a =
    74.5000
height_b =
    80.9305
```

Problem 14

Script file:

```
clear, clc
vrun=3; vswim=1; L=48; ds=30; dw=42;
y=20:1:48;
ls = sqrt(y.^2+ds^2);
lw = sqrt((L-y).^2+dw^2);
t=ls/vrun + lw/vswim;
[tmin indx] = min(t);
min_t=t(indx)
y_at_min=y(indx)
phi = atan(y_at_min/ds);
alpha = atan((L-y_at_min)/dw);
sin_ratio=sin(phi)/sin(alpha)
speed_ratio=vrun/vswim
```

Command Window:

```
min_t =
    59.2946
y_at_min =
    37
sin_ratio =
    3.0658
speed_ratio =
    3
```

Discussion: The minimum time is 59.29 seconds with the lifeguard entering the water at 37 m. Snell's law seems only approximately satisfied, but this is due to the relatively large increment in y . The ratio converges to Snell's law as the increment decreases. For example, decreasing the increment to .01 gives a sine ratio of 2.9996.

Problem 15

Script file:

```
clear, clc
H=70; h=900;
x=50:.5:1500;
theta=atan(h./x)-atan((h-H)./x);
[max_th indx]=max(theta);
disp('The best target view occurs at a distance in feet of')
disp(x(indx))
```

Command Window:

```
The best target view occurs at a distance in feet of
    864.5000
```


Problem 16

Script file:

```
clear, clc
load stress_data.txt
M=stress_data(1); b=stress_data(2); t=stress_data(3); a=stress_data(4);
alpha=a/b; beta=pi*alpha/2;
C=sqrt(tan(beta)/beta)*((0.923+0.199*(1-sin(beta))^2)/cos(beta));
sigma=6*M/(t*b^2);
K=C*sigma*sqrt(pi*a);
fprintf('The stress intensity factor for a beam that is %.2f m wide',b)
fprintf(' and %.2f m thick\nwith an edge crack of %.2f m and an',t,a)
fprintf(' applied moment of %.0f is %.0f pa-sqrt(m).\n',M,K)
```

Text File (stress_data.txt):

```
20 .25 .01 .05
```

Command Window:

The stress intensity factor for a beam that is 0.25 m wide and 0.01 m thick with an edge crack of 0.05 m and an applied moment of 20 is 82836 pa-sqrt(m).

Problem 17

Script file:

```
clear, clc
v=50; rho=2000; h=500;
t_90=pi*rho/(2*v);
t=linspace(0,t_90,15);
alpha=v*t/rho;
r=sqrt(rho^2 + (h+rho)^2 - 2*rho*(rho+h)*cos(alpha));
theta=90-asind(rho*sin(alpha)./r);
fprintf('For a plane flying at a speed of %.0f m/s in a circular path ',v)
fprintf('of radius %.0f m\ncentered above the tracking station and ',rho)
fprintf('%.0f m above the station at its lowest point:\n\n',h)
%fprintf accesses elements column by column
%can also use disp as shown in problem 11
tbl=[t;theta;r];
fprintf('      Time      Tracking      Distance\n')
fprintf('      (s)      Angle (deg)      (m)\n')
fprintf('      %4.1f      %4.1f      %6.1f\n',tbl)
```

Command Window:

For a plane flying at a speed of 50 m/s in a circular path of radius 2000 m centered above the tracking station and 500 m above the station at its lowest point:

Time	Tracking	Distance
(s)	Angle (deg)	(m)
0.0	90.0	500.0
4.5	66.4	559.4
9.0	51.0	707.6
13.5	42.8	900.6
18.0	38.8	1113.7
22.4	37.2	1335.2
26.9	36.9	1559.4
31.4	37.5	1783.0
35.9	38.7	2003.8
40.4	40.3	2220.3
44.9	42.2	2431.3
49.4	44.3	2635.8
53.9	46.5	2832.8
58.3	48.9	3021.6
62.8	51.3	3201.6

Problem 18


Script file:

```
clear, clc
C=13.83; Eg=0.67; k=8.62e-5;
T=xlsread('Germanium_data.xlsx');
sigma=exp(C-Eg./(2*k*T));
tbl=[T sigma];
disp('          Intrinsic')
disp('    Temperature  Conductivity')
disp('    deg K        (ohm-m)^-1')
%can also use disp as shown in problem 11
fprintf('    %4.0f        %5.1f\n',tbl')
```

Command Window:

Temperature	Intrinsic
deg K	(ohm-m) ⁻¹
400	61.2
435	133.7
475	283.8
500	427.3
520	576.1
545	811.7

Excel File:



	A	B
1	400	
2	435	
3	475	
4	500	
5	520	
6	545	
7		

Problem 19

Script file:

```
clear, clc
rho=input('Please input the fluid density in kg/m^3: ');
v=input('Please input the fluid velocity in m/s: ');
d_ratio=input('Please input the pipe diameter ratio as a vector [x x x]: ');
delP=0.5*(1-d_ratio.^2).^2*rho*v^2;
fprintf('\nFor gasoline with a density of %.0f kg/m^3 and a flow ',rho)
fprintf('velocity of %.1f m/s\n\n',v)
tbl=[d_ratio;delP];
disp('          delta P')
disp('    d/D          (Pa)')
fprintf('    %3.1f          %6.1f\n',tbl)
```

Command Window:

```
Please input the fluid density in kg/m^3: 737
Please input the fluid velocity in m/s: 5
Please input the pipe diameter ratio as a vector [x x x]: [.9:-.1:.4 .2]
```

For gasoline with a density of 737 kg/m³ and a flow velocity of 5.0 m/s

d/D	delta P (Pa)
0.9	332.6
0.8	1193.9
0.7	2396.2
0.6	3773.4
0.5	5182.0
0.4	6500.3
0.2	8490.2

Problem 20

Script file:

```
clear, clc
sigma=5.669e-8;
T1=input('Please input the temperature of plate 1 in deg K: ');
T2=input('Please input the temperature of plate 2 in deg K: ');
a=input('Please input the radius of plate 1 in m: ');
b=input('Please input the radius of plate 2 in m: ');
c=input('Please input the distance between plate 1 and plate 2 in m: ');
X=a./c; Y=c/b; Z=1+(1+X.^2).*Y.^2;
F_1_2 = 0.5*(Z-sqrt(Z.^2-4*X.^2.*Y.^2));
q=sigma*pi*b^2*F_1_2*(T1^4-T2^4);
fprintf('\nFor circular plate 1 with radius %i m and temperature %i',a,T1)
fprintf(' deg K\nand circular plate 2 with radius %i m and temperature',b)
fprintf(' %i deg K\n',T2)
tbl=[c;q];
fprintf('\n
          Separation      Radiation\n')
fprintf('          (m)          (Watts)\n')
fprintf('          %4.1f          %6.0f\n',tbl)
```

Command Window:

```
Please input the temperature of plate 1 in deg K: 400
Please input the temperature of plate 2 in deg K: 600
Please input the radius of plate 1 in m: 1
Please input the radius of plate 2 in m: 2
Please input the distance between plate 1 and plate 2 in m: 10.^(-1:1)
```

```
For circular plate 1 with radius 1 m and temperature 400 deg K
and circular plate 2 with radius 2 m and temperature 600 deg K
```

Separation	Radiation Heat Exchange
(m)	(Watts)
0.1	-18461
1.0	-14150
10.0	-706

Problem 21

Script file:

```
clear, clc
x1=input('Please enter the coordinates of point 1 as a vector [x x]: ');
x2=input('Please enter the coordinates of point 2 as a vector [x x]: ');
x3=input('Please enter the coordinates of point 3 as a vector [x x]: ');
A=2*[x1(1)-x2(1) x1(2)-x2(2); x2(1)-x3(1) x2(2)-x3(2)];
B=[x1(1)^2+x1(2)^2-x2(1)^2-x2(2)^2; x2(1)^2+x2(2)^2-x3(1)^2-x3(2)^2];
C=A\B;
r=sqrt((x1(1)-C(1))^2 + (x1(2)-C(2))^2);
fprintf('\nThe coordinates of the center are (%.1f, %.1f) ',C)
fprintf('and the radius is %.1f.\n',r)
```

Command Window:

```
Please enter the coordinates of point 1 as a vector [x x]: [10.5, 4]
Please enter the coordinates of point 2 as a vector [x x]: [2, 8.6]
Please enter the coordinates of point 3 as a vector [x x]: [-4, -7]
```

The coordinates of the center are (2.5, -0.6) and the radius is 9.2.

Problem 22

Script file:

```
clear, clc
T=[cosd(48.81) 1 0 0 0 0 0 0 0
    0 -1 0 0 cosd(48.81) 1 0 0 0
    0 0 1 0 sind(48.81) 0 0 0 0
    -cosd(48.81) 0 0 1 0 0 0 0 0
    -sind(48.84) 0 -1 0 0 0 0 0 0
    0 0 0 -1 -cosd(48.81) 0 0 0 0
    0 0 0 0 -sind(48.81) 0 -1 0 -sind(45)
    0 0 0 0 0 0 0 0 sind(45)
    0 0 0 0 0 0 0 -1 -cosd(45)];
A=[0; 0; 0; 0; 1800; 1200; 0; 1500; 0];
N=1:9;
F=T\A;
tbl=[N;F'];
disp(' ')
disp(' Member Force')
disp(' No. lbf')
fprintf(' %1i %7.1f\n',tbl)
```

Command Window:

Member No.	Force lbf
1	-2106.6
2	1387.3
3	-214.0
4	-1387.3
5	284.4
6	1200.0
7	-1714.0
8	-1500.0
9	2121.3

Problem 23

Script file:

```
clear, clc
T=[.7071 1 0 0 0 0 0 0 0 0 0 0 0; 0 -1 0 0 0 1 0 0 0 0 0 0 0; ...
    0 0 1 0 0 0 0 0 0 0 0 0 0; -.7071 0 0 1 .6585 0 0 0 0 0 0 0 0; ...
    .7071 0 1 0 .7526 0 0 0 0 0 0 0 0; 0 0 0 -1 0 0 1 .6585 0 0 0 0 0; ...
    0 0 0 0 0 0 0 .7526 1 0 0 0 0; 0 0 0 0 -.6585 -1 0 0 0 1 0 0 0; ...
    0 0 0 0 .7526 0 0 0 1 0 0 0 0; 0 0 0 0 0 0 -1 0 0 0 .7071 0 0; ...
    0 0 0 0 0 0 0 0 0 0 .7071 1 0; 0 0 0 0 0 0 0 0 .7526 0 0 0 1 0; ...
    0 0 0 0 0 0 0 0 0 0 .7071 0 1];
A=[0; 0; 2000; 0; -2000; 0; 0; 0; 1000; 0; -3000; 2000; 0];
N=1:13; F=T\A;
tbl=[N;F'];
disp(' ')
disp(' Member Force')
disp(' No. lbf')
fprintf(' %2i %7.1f\n',tbl)
```

Command Window:

Member No.	Force lbf
1	-6741.2
2	4766.7
3	2000.0
4	-5437.5
5	1018.7
6	4766.7
7	-5233.3
8	-310.0
9	233.3
10	5437.5
11	-7401.1
12	2233.3
13	5233.3

Problem 24

Script file:

```
clear, clc
x=[-2.6 0.5 1.5 3.5]; y=[-68; 5.7; 4.9; 88]; power=3:-1:0;
X=[x(1).^power; x(2).^power; x(3).^power; x(4).^power];
coefs=X\y;
fprintf('\nThe equation is f(x)=%.3fx^3 + %.3fx^2 + %.3fx + %.3f\n',coefs)
```

Command Window:

The equation is $f(x)=3.297x^3 + -4.016x^2 + -3.483x + 8.033$

Problem 25

Script file:

```
c=1; t=0.2;
x=[.15 .35 .5 .7 .85]; y=[.08909 .09914 .08823 .06107 .03421];
A=sqrt(x/c); B=x/c; C=(x/c).^2; D=(x/c).^3; E=(x/c).^4;
X=[A' B' C' D' E']; Y=0.2*y'/(t*c);
coefs=X\Y;
fprintf('The coefficients are:\n')
fprintf('a0=%.4f, a1=%.4f, a2=%.4f, a3=%.4f, a4=%.4f\n',coefs)
```

Command Window:

The coefficients are:

a0=0.2969, a1=-0.1258, a2=-0.3526, a3=0.2861, a4=-0.1025

Problem 26

Script file:

```
clear, clc
X=[1 2 1 1; 2 3 0 1; 1 4 1 0; 1 3 2 0]; Y=[5; 12; 11; 8];
coefs=X\Y;
fprintf('The scoring values are:\nEagle: %.1f\nBirdie: %.1f\n',coefs(1:2))
fprintf('Bogey: %.1f\nDouble: %.1f\n',coefs(3:4))
```

Command Window:

The scoring values are:

Eagle: 4.0

Birdie: 2.0

Bogey: -1.0

Double: -2.0

Problem 27

Script file:

```
clear, clc
X=[1 0 0 -1 0 0 0; 1 0 0 0 -1 0 0; 0 1 0 0 0 -1 0; 0 3 0 0 -4 -1 -1; ...
   0 0 1 0 0 0 -2; 0 -1 1 -2 2 0 0; 1 0 0 0 0 0 0];
disp('Try a=1')
Y=[0; 0; 0; 0; 0; 0; 1];
coefs=(X\Y)'
disp('Try a=2')
Y=[0; 0; 0; 0; 0; 0; 2];
coefs=(X\Y)'
disp('Try a=3')
Y=[0; 0; 0; 0; 0; 0; 3];
coefs=(X\Y)'
```

Command Window:

```
Try a=1
coefs =
    1.0000    2.6667    2.6667    1.0000    1.0000    2.6667    1.3333
Try a=2
coefs =
    2.0000    5.3333    5.3333    2.0000    2.0000    5.3333    2.6667
Try a=3
coefs =
    3.0000    8.0000    8.0000    3.0000    3.0000    8.0000    4.0000
```

Problem 28

Script file:

```
Ts=40:-10:-40; T=[Ts;Ts;Ts;Ts;Ts;Ts];
vs=[10:10:60]'; v=[vs, vs, vs, vs, vs, vs, vs, vs, vs];
%if using disp for table need round function
Twc=35.74+0.6215*T-35.75*v.^0.16+0.4275*T.*v.^0.16;
tbl=[vs Twc]';
fprintf('                Temperature (F)\n          ')
fprintf('    %3i',Ts)
fprintf('\n    Speed\n    (mi/hr)\n')
fprintf('    %3.0f %3.0f %3.0f %3.0f %3.0f %3.0f %3.0f %3.0f %3.0f\n',tbl)
fprintf('    %3.0f %3.0f\n',tbl)
```


Command Window:

	Temperature (F)								
	40	30	20	10	0	-10	-20	-30	-40
Speed (mi/hr)									
10	34	21	9	-4	-16	-28	-41	-53	-66
20	30	17	4	-9	-22	-35	-48	-61	-74
30	28	15	1	-12	-26	-39	-53	-67	-80
40	27	13	-1	-15	-29	-43	-57	-71	-84
50	26	12	-3	-17	-31	-45	-60	-74	-88
60	25	10	-4	-19	-33	-48	-62	-76	-91

Problem 29

Script file:

```
clear, clc
a_b=0:.05:.95;
C=0.265*(1-a_b)+(0.857+0.265*a_b)./(1-a_b).^1.5;
tbl=[a_b;C];
fprintf('    a/b          C\n')
fprintf('    %4.2f      %6.3f\n',tbl)
```

Command Window:

a/b	C
0.00	1.122
0.05	1.192
0.10	1.273
0.15	1.370
0.20	1.484
0.25	1.620
0.30	1.785
0.35	1.985
0.40	2.231
0.45	2.539
0.50	2.931
0.55	3.441
0.60	4.122
0.65	5.063
0.70	6.424
0.75	8.512
0.80	12.005
0.85	18.669
0.90	34.669
0.95	99.183